

“Built To Last Forever”





Single Component



Good Coverage



Non-Slump

ultra LITE Tile

Type-1

EuroBuilt - Ultra Lite tile is cement based polymer added tile adhesive made for fixing small and medium size tiles in internal area on floor for renovation as well as fresh work.

Product Features:

- Tiles: Ceramic tiles
- Surfaces: Floors
- Location: Interior
- Color : White & Grey
- Packaging: 20 Kg
- Coverage: 20 kg material will cover approx. 50 sq ft on a consistently flat surface.

Technical Data:

- Standards : IS TYPE 1
- Setting Time : 24 Hrs
- Pot Life : 1/2 hr
- Tensile Bond Strength: $\geq .75$ KN after 28 days.

Installation:

Water Ratio: 1 bag to 5 litres of clean water.

Mixing: Add tile adhesive to water and mix to thick smooth consistency with machine. Allow to stand for 5 minutes & stir the mix again & the adhesive is ready to use. (Don't add more water to the mixture once the adhesive has exceeded its pot life.)

Application: Use 6 to 10 mm notched trowel for floors. Do not apply EuroBuilt Ultra lite tile at a bed thickness greater than 5 mm. The most important standard to keep in mind is to insure that the tile is completely bedded in adhesive with 100% coverage.



ultra BOND FIX C1



Extended Open Time



All Tile Types



Stronger Bond

EuroBuilt - Ultra Bond Fix is polymer fortified wall & floor tile adhesive, which is specially formulated to produce higher bond strength suitable for fixing all types of tiles including dense bodied and fully vitrified tiles.

Product Features:

Tiles: Ceramic tiles, fully vitrified tiles and porcelain.

Surfaces: Walls and Floors

Location: Interior and exterior (providing surfaces are not subject to movement)

Color : White & Grey

Packaging: 20 Kg

Coverage: 20 kg material will cover approximately 50 sq ft on a consistently flat surface.

Installation:

Water Ratio: 1 bag to 5 litres of clean water.

Mixing: Add tile adhesive to water and mix to thick smooth consistency with machine. Allow to stand for 5 min & stir the mix again and the adhesive is ready to use. (Don't add more water to the mixture once the adhesive has exceeded its pot life.)

Technical Data:

European standards : EN C1 E

Setting Time : 24 Hrs

Pot Life : 1 hr

Tensile Bond Strength: ≥ 1.0 N/mm² after 28 days.



Application: Use 10 mm notched trowel for floors, 6 mm notched trowel for walls. (10 mm notched trowel is recommended for larger wall tiles.)
Do not apply EuroBuilt Ultra Bond Fix at a bed thickness greater than 7 mm.
The most important standard to keep in mind is to insure that the tile is completely bedded in adhesive with 100% coverage.



Non- Shrink



Water Resistant



Gel Based

ultra GRIP

C2

EuroBuilt - Ultra Grip is High Tensile Strength Tile Adhesive, polymer fortified for wall & floor. It has extremely high tensile strength for fixing large format tiles, stone, marble & porcelain tiles.

Product Features:

- Tiles:** Larger format tiles, stone, marble Porcelain tiles.
- Surfaces:** Walls and Floors
- Location:** Interior and exterior.
- Color :** White & Grey
- Packaging:** 20 Kg
- Coverage:** 20 kg material will cover approx. 50 sq ft on a consistently flat surface.

Installation:

- Water Ratio:** 1 bag to 5 litres of clean water.
- Mixing:** Add tile adhesive to water and mix to thick smooth consistency with machine. Allow to stand for 5 minutes & stir the mix again & the adhesive is ready to use. (Don't add more water to the mixture once the adhesive has exceeded its pot life.)

Technical Data:

- European standards :** EN C2 TE
- Setting Time :** 24 Hrs
- Pot Life :** 1 hr
- Tensile Bond Strength:** ≥ 1.3 N/mm² after 28 days.



- Application:** Use 10 mm notched trowel for floors, 6 mm notched trowel for walls. 10 mm notched trowel is recommended for larger wall tiles. Do not apply EuroBuilt Ultra Grip at a bed thickness greater than 7 mm. The most important standard to keep in mind is to insure that tile is completely bedded in adhesive with 100% coverage.

ultra FLEX

S1



Highly Flexible



Water Resistant



Non-Slump

EuroBuilt - Ultra Flex is a high performance, flexible adhesive with a high polymer loading. It is designed to install glass mosaics, stone, porcelain, fully vitrified and other dense bodied tiles over substrates.

Product Features:

- Tiles:** Larger format tiles, stone, marble, mosaic, ceramic tiles and fully vitrified tiles.
- Surfaces:** Walls and Floors
- Location:** Interior and Exterior
- Color :** White & Grey
- Packaging:** 20 Kg
- Coverage:** 20 kg material will cover approximately 50 sq ft on a consistently flat surface.

Installation:

Water Ratio: 1 bag to 5 litres of clean water.

Mixing: Add tile adhesive to water and mix to thick smooth consistency with machine. Allow to stand for 5 min & stir the mix again and the adhesive is ready to use. (Don't add more water to the mixture once the adhesive has exceeded its pot life.)

Technical Data:

- European standards :** C2 TE S1
- Setting Time :** 24 Hrs
- Pot Life :** 1 hr
- Tensile Bond Strength:** ≥ 3 N/mm² after 28 days.



Application: Use 10 mm notched trowel for floors, 6 mm notched trowel for walls. (10 mm notched trowel is recommended for larger wall tiles.) Do not apply EuroBuilt Ultra Flex at a bed thickness greater than 7 mm. The most important standard to keep in mind is to insure that the tile is completely bedded in adhesive with 100% coverage.



Colour Fast



Water & Shock
Resistant



Non Cracking &
Powdering



Easy To Clean

ultra EPOXY GROUT

EuroBuilt- Epoxy Grout is stain free, colour-fast chemical resistant for use with ceramic & vitrified tiles, marble and stone. It is a 2 AND 3 component epoxy grout consisting hardener, resin and filler of various types of color. EURO BUILT epoxy grout suitable for all type of ceramic tiles in green buildings. It can be applied on horizontal and vertical, Interior & exterior, dry, wet, and submerged conditions in residential and commercial areas, EURO BUILT epoxy grout used with ceramic, porcelain, vitrified, natural, glass mosaic, granite and stone tile, in different size of filling widths.



Stain Resistant



Chemical &
Temperature
Resistant

Technical Data:

Density :	2200 TO 2300 Kg/m ³
Expansion :	0.1 to 0.5%
Specific Gravity :	1.75
Shore D Hardness :	> 70
Drying Time :	+/- 45 minutes and varies depending upon atmospheric temperature.
Joint Width :	2 - 20 mm

Mixing

Empty entire contents of Euro Built epoxy Grout Part "A" and Part "B" in container mix to a uniform consistency. Use a plastic sheet as a drip cloth. Use standard epoxy grouting techniques to work with Euro build Epoxy Grout into tile joints. Be sure all grout joints are packed full. Remove as much excess material as possible before initial cleaning with grout float. Do not leave excess grout on the face of tiles.



Cleaning: Remove excess grout from the face of the tiles with the edge of the grout float. Hold the float at a 90° angle and pull it diagonally across the joints and tile to avoid pulling out the material.
Initial Cleaning: After 30-45 min of the application of the grout scrub the surface of the tile & joint with clean water and scrubber provided to remove any excess grout. Then take a clean thick white towel and drag across the tile to remove any residual. **Final Cleaning:** within 24 hours do a second cleaning with normal soap detergent to remove any haze

® Tile GROUT

EuroBuilt Tile Grout is an unsanded, superfine product designed in different color for use with polished porcelain, mosaic or soft-glazed tiles with joint widths between 2 mm and 8 mm. It is formulated with excellent resistance to a broad range of mould and bacteria, and a blend of high strength Portland cement provides a grout joint that is dense, hard and durable.



Colour Fast



Water Resistant (Hydrophobic)



Weather Resistant



Stain Resistant



Non Shrinking



Smooth & Gloss Finish

Features & Benefits:

Superfine -

A very smooth product that gives a more aesthetically pleasing finish.

Enhanced formula -

Now with improved colour integrity and consistency.

Versatile -

Excellent for wet and dry, interior and exterior areas.

For grout joints between 2 mm to 8 mm.

Easy to mix, creamy consistency and high productivity grout.

Can be applied on the wall and floor.

Use approximate 300 to 400 ml of water or Euro Built Thick Admix for 1 kg Euro Build Tile Grout powder. Mix it well until smooth lump free paste is obtained leave it for 5 minutes then mix it again ready to use.

Application: Spread the mixed grout with a sharp, firm, rubber grout float using diagonal strokes to pack the joints. Ensure the joint is filled and the grout does not bridge the joint.





Highly Durable



Superior Finish



Excellent workability



Graded sand with no silt content



Compact plaster to effectively reduce void gaps.

ultra SMOOTH Ready Mix Plaster

EuroBuilt-Ultra smooth ready mix plaster is blend of Portland cement, fine graded sand, high quality polymer additives in the right proportion. It is ready to use by simply mixing water at site and can be easily applied on brick, blocks and concrete surfaces.

Product Benefits :

Reduce Cost: Ultra smooth ready mix plaster with its greater compactness and strength substantial reduce the repair and maintenance cost of the building while enhancing the life of plaster and paint on it. The pace of the construction is largely depends on how quickly the plaster is applied and sets.

Saves time: With simple opening of bag and mixing with machine and it sets faster. This means construction get quicker and gets completed in schedule timeline.

Saves water: Water consumption during construction is less as compared to traditional plaster.

Excellent Workability: It is a ready to use plaster with smart and smother finish.

Coverage:

With 40 kg bag

10-12 mm plaster of AAC blocks 17-18 sq ft.

10-12 mm plaster on clay bricks 14-15 Sq ft.

18 mm on AAC blocks 11 sq ft.

25 mm on brick wall 6-7 sq ft.

10 mm on RCC 20-22 sq ft.



Note: coverage is inductive figure. It depends manly on substrate conditions and natural elements plaster more than 12 mm should be done in multiple coats.

ultra FINISH WALL PUTTY

EuroBuilt-Ultra Finish wall putty comprises micronized particles that are much finer and far lighter than ordinary wall putties. With the blend of polymers it is easier to mix and generate a super smooth paste that results in smoother walls and 25% higher coverage than other putties. Euro build Ultra Finish wall putty provides a better skim coat for fresher looking colors and consumes less paint. Due to polymers it has high resistance to moisture, efflorescence and fungus, which ensures better longevity.



Less Material Use



Long Lasting



Fungus Free



Non Cracking & Powdering



Dust-less

Technical Data:

Dry density:	830 kg/cum (+/- 5%)
Initial setting time:	120 - 150 mins
Final setting time:	300 - 360 mins
Pot life:	2.5 hrs
Coating thickness:	0.8 - 1.2 mm
Coverage*:	15 sq.ft./kg Ideal for use at 27° C to 30° C

* When applied under controlled environment by skilled applicator and with proper tools

Mixing:

- 1.Fill a clean pot with potable water measuring 45% the weight of putty (1 kg Euro Build Smooth Putty : 0.45 litres water.)
- 2.Pour Euro Build Ultra Finish wall putty in the pot filled with water. Mix and knead slowly to form a homogeneous paste. Let the mixture stand for 10 minutes.
- 3.Mix the paste again without adding more water.
- 4.Evenly apply the first coat Euro Build Ultra Finish wall Putty on the surface. Apply from bottom to top, followed by left to right direction without leaving stroke marks.
- 5.Remove loose particles if any prior to application of second coat Repeat action (as per sr. no. 4) for application of second coat.





PH Neutral Formula



Gentle

ultra SHINE Tile Cleaner

EuroBuilt - Ultra Shine Tile Cleaner
Designed to clean every day mess on natural stone and tiles.



Product Features:

- Remove everyday spills, dirt & grease.
- Ready to use.
- Gentle formula.
- Neutral PH.
- Can be used as daily cleaner.
- 1 Ltr bottle.

How To Use:

1. Test the surface with applying magic clean in a corner before using and observe for 24 Hrs for any change in color.
2. Pour Ultra Shine Tile Cleaner in utensil and dilute it. With Water if required.
3. Apply it on the surface with clean cloth, after 5 mins brush it.

ultra THICK ADMIX



Euro Built Ultra Thick Admix

Increases the performance and strength of your Euro built grout. It seals, protects and strengthens the grout. It is suitable for use in interior and exterior locations in both dry and wet services conditions, including swimming pools.

Instructions for use

1. Shake the bottle before use.
2. For 1 kg Grout pack application, dilute 1 part of Euro Built thick Admix with 2 to 3 parts of clean water.
3. Mix it well until smooth lump free paste is obtained leave it for 5 minutes then mix it again.



www.eurobuilt.in



Address:

303, Unnati Tower, Central Spine,
Vidyadhar Nagar, Jaipur
Rajasthan 302023

info@eurobuilt.in

Customer care: 7508131331

